

SIDE WALL MOUNTING BRACKET

OVERHEAD TRACT

ADJUSTABLE HEIGHT PENDANT BOLT

STRUCTURAL AND ANCHORAGE FRAMING BY OTHERS

4 WHEEL HANGER

RADIATION SOURCE SIDE

RAY-BAR INDUSTRIAL SLIDING SHIELDED DOOR, (MEDICAL SLIDER DOOR SIMILIAR)

LEAD, AS SPECIFIED

DOOR OPENING

CORE MATERIAL

STEEL FACE

FINISH FLOOR, BY OTHERS

VERIFY

VARIES

SECTION AT HEAD

FLOOR TRENCH, (NOT REQUIRED IN MOST MEDICAL IMAGING APPLICATIONS WHEN USING RAY-BAR SHIELDED FLOOR SWEEP)

VERIFY

VERIFY


SECTION AT SILL

NOTES:

1. GALVANIZED STEEL WITH PRIMER FINISH.
2. 99.9% PURE LEAD SHIELDING MEETING FEDERAL SPEC. QQ-L-201F GRADE C AND ASTM B749 TYPE L51121.
3. LEAD SHIELDING THICKNESS AS SPECIFIED BY PROJECT RADIATION PHYSICIST.
4. CUSTOMER / INSTALLER MUST VERIFY LEAD SHIELDING EQUIVALENCY REQUIREMENT PRIOR TO ORDERING.
5. DOOR MAY REQUIRE POWER OPERATION (BY OTHERS)

1 RAY-BAR INDUSTRIAL LEAD LINED DOOR
6" = 1'-0"

Terms of Use: Certain designs and concepts are the exclusive proprietary property and work product of Ray-Bar Engineering provided in good faith as a courtesy for the architectural design of projects specifying, incorporating and utilizing genuine Ray-Bar products and assemblies. Ray-Bar designs are not to be copied, altered, plagiarized or utilized in any competitive or detrimental manner against Ray-Bar as protected by law and/or copyrights. "All Rights Reserved"

	JOB NAME:	
	LOCATION:	
	ROOM NUMBER:	
	SHEET ____ OF ____:	
LEAD LINED SLIDING DOOR SECTION		

RAY-BAR ENGINEERING CORP.
 Toll Free: 1(800) 444-XRAY / 1(800) 444-9729
 Telephone: (626) 969-1818
 24 Hour Fax: 1(800) 333-XRAY / 1(800) 333-9729
 website: www.raybar.com

2012-05-10
 SCALE
 6" = 1'-0"
LLSD-1