

RAY-BAR MOBILE X-RAY CONTROL BARRIERS:

1. STANDARD: 1/16" - 1.6MM - #4 LEAD SHIELDING.
2. HIGHER SHIELDING LEVELS AVAILABLE.
3. AVAILABLE IN:
STANDARD WHITE OR GRAY FINISH
SOLID LAMINATE COLORS
SOLID POWDER COATED COLORS
4. CLEAR X-RAY LEAD GLASS.
5. X-RAY SAFETY GLASS IN BARRIER TYPES M5 AND M6.
6. CUSTOM SIZES AND CONFIGURATIONS ARE ALSO AVAILABLE.


SPECIFICATION NOTES:

ALL RAY-BAR SHEET LEAD IS 99.9% PURE MEETING FEDERAL SPEC. QQ-L-201F GRADE C AND ASTM B749 TYPE L51121 AND ALL APPLICABLE NCRP REPORTS.

NOTE:

CUSTOMER / INSTALLER MUST VERIFY LEAD SHIELDING EQUIVALENCY REQUIREMENT PRIOR TO ORDERING.

Terms of Use: Certain designs and concepts are the exclusive proprietary property and work product of Ray-Bar Engineering provided in good faith as a courtesy for the architectural design of projects specifying, incorporating and utilizing genuine Ray-Bar products and assemblies. Ray-Bar designs are not to be copied, altered, plagiarized or utilized in any competitive or detrimental manner against Ray-Bar as protected by law and/or copyrights. "All Rights Reserved"

	JOB NAME:	
	LOCATION:	
	ROOM NUMBER:	
	SHEET ____ OF ____:	
MOBILE X-RAY CONTROL BARRIERS		

RAY-BAR ENGINEERING CORP.
Toll Free: 1(800) 444-XRAY / 1(800) 444-9729
Telephone: (626) 969-1818
24 Hour Fax: 1(800) 333-XRAY / 1(800) 333-9729
website: www.raybar.com

2012-05-10
SCALE
MXB-1